



## Key Features

- ◎ High sensitivity, multi output power
- ◎ Multi wavelengths optional, up to four wavelengths on two ports
- ◎ Automatic power-off, off time setting range 30~90mins
- ◎ Low battery alarm
- ◎ LCD display
- ◎ New-type conductive rubber switch, suitable for different operation environments.

## Technical Specifications

Parameter	Technical parameters						
Model	3E03	3E04	3E05	3E06	3E07	3E08	
Working wavelength(nm)	1310/1550	650/1310/1550	850/1310/1550	650/1300	1310/1490/1550	1310/1550/1625	
Output power (dBm)	850/1300/1310/1550/1490/1625: -6 (error: ±0.2)						
Model	3E13	3E14	3E15	3E16	3E17	3E18	3E19
Working wavelength(nm)	1310/1550	650/1310/1550	850/1310/1550	850/1300	1490/1310/1550	1625/1310/1550	850/1300/ 1310/1550
Output power (dBm)	1310/1550: 0, -3, -6; 650: >0; 850/1300/1490/1625: -6 (error: ±0.2)						-6
Output Tone	850/1300/1310/1550 /1490/1625: CW, 270Hz, 1KHz, 2KHz;						650: CW
Spectrum width	≤ 5 nm						
Output stability	±0.03dB/15min; ±0.05dB/8h						
Optical identifying distance	5km; 10km /15km optional (650nm)						
Display	LCD						
Auto turn-off time	30~99mins or none						
Interface	FC, SC, ST						
Power supply	2X1.2V AA nickel-hydrogen rechargeable batteries						
Luminous parts	LD						
Operating temperature	-10~+50℃						
Storage temperature	-40~+70℃						
Dimension	L×W×H:140×72×38mm						
Weight	0.3kg						